

everything³

HPT¹

30-50K
THREE PHASE 4MPPTS



Peak Efficiency
98.8 %



Max. DC Overload
50 %



MES + FCT + CRM
Infrastructure



Easy to Install and
Service

HYPONTECH

 **HYPON.COM**
© HYPONTECH SOLAR ENERGIZING FUTURE

EN 20241210



MODEL	HPT-30K	HPT-33K	HPT-36K	HPT-40K	HPT-50K
PV INPUT					
Max.PV Power / W	49500	49500	54000	60000	65000
Max. Input Voltage / V	1100	1100	1100	1100	1100
MPP Voltage Range/ V	150-1000	150-1000	150-1000	150-1000	150-1000
Start Up Voltage / V	150	150	150	150	150
Rated Input Voltage /V	620	620	620	620	620
Max. Input Current / A	30/30/30	30/30/30	30/30/30	30/30/30/30	30/30/30/30
Max. Short Circuit Current / A	45/45/45	45/45/45	45/45/45	45/45/45/45	45/45/45/45
No. of MPPTs/No. Strings Per MPPT	3/2	3/2	3/2	4/2	4/2
AC OUTPUT					
Rated Power / W	30000	33000	36000	40000	50000
Max. Apparent Power / VA	33000	36300	39600	44000	55000
Rated Grid Voltage / V	380/400	380/400	380/400	380/400	380/400
Grid Connection	3L-N-PE or 3L-PE	3L-N-PE or 3L-PE	3L-N-PE or 3L-PE	3L-N-PE or 3L-PE	3L-N-PE or 3L-PE
Rated Grid Frequency / Hz	50/60	50/60	50/60	50/60	50/60
Max. Output Current / A	50	55	60	66.7	80
Power Factor	0.8ind - 0.8cap	0.8ind - 0.8cap	0.8ind - 0.8cap	0.8ind - 0.8cap	0.8ind - 0.8cap
TH Di @ Rated Power	<3%	<3%	<3%	<3%	<3%
EFFICIENCY					
Max. Efficiency	98.7%	98.7%	98.7%	98.7%	98.8%
Euro. Efficiency	98.3%	98.3%	98.3%	98.3%	98.4%
MPPT Efficiency	>99.9%	>99.9%	>99.9%	>99.9%	>99.9%
PROTECTION FUNCTION					
Anti-Islanding Protection			Integrated		
PV String Input Reverse Polarity Protection			Integrated		
Insulation Resistance Detection			Integrated		
Residual Current Monitoring Unit			Integrated		
Output Over Current Protection			Integrated		
Output Short Circuit Protection			Integrated		
Over Voltage Protection			Integrated		
Surge Protection	DC: Type II /AC: Type II				
GENERAL DATA					
Dimensions (W*H*D) / mm	580*435*242				
Weight / kg	38	38	38	40	40
User Interface	LCD&LED				
PV Connection Type	MC4 (D4, SUNCLIX, H4 optional)				
Communication with Cloud	RS485/Wi-Fi/4G/LAN (optional)				
Cooling Method	Smart Fan Cooling				
Operating Ambient Temperature / °C	-25 ~ +60				
Relative Humidity / %	0-100				
Max. Operating Altitude / m	2000 (>2000 Derating)				
Protection Class (IEC 60529)	IP65				
Climatic Category (IEC 60721-3-4)	4K4H				
Topology	Transformerless				
Night Consumption / W	<1				