

monitor
module
HED



Data Security



Remote Upgrade



**Protection Class
IP65**



Quick and Easy Installation



Support Wi-Fi / 4G

HYPONTECH
     **HYPON.COM**
 ©HYPONTECH SOLAR ENERGIZING FUTURE

EN 20250410

HED				
MODEL	HED-WF	HED-4G(CN)	HED-4G(EU)	HED-LAN
ELECTRICAL DATA				
Power Supply	DC 4.5 - 18V			
GENERAL DATA				
Max. Number of Inverters	1			
Inverter Communication Interface	RS485			
Antenna	Internal Integrated			
Enthernet Interface	/	/	/	LAN (100Mbps)
LED Indicator	1 (for Web Status)			
Serial Communicaiton Rate / bps	9600			
Communicaiton Distance / m	<=100	<=100	/	<=100
Data Intervals	5 Mins (0.5-5Mins can be adjusted)			
Parameters Setting	Bluetooth/Web/APP	Web/APP	Web/APP	Web/APP
Data Access	Web server			
ENVIRONMENTAL DATA				
Operating Temperature Range / °C	-20 ~ +60			
Operating Humidity	0 ~ 100%			
Storage Temperature Range / °C	-35 ~ +70			
Degree Of Protection	IP65			
MECHANICAL DATA				
Dimensions (W*H*D) / mm	97*46*28			
Weight / g	60			
OTHERS				
Flame Retardant Grade	UL94 V-0			
UV Protection Grade	F1			
Installation Method	Plug-in			
STANDARD				
Cetification	RED/FCC/CE/RoHS			