

monitor
module

HED



Data
Security



Remote
Upgrade



Protection Class
IP65



Quick and Easy
Installation



Support Wi-Fi
/ 4G

HYPONTECH

 HYPON.COM
©HYPONTECH SOLAR ENERGIZING FUTURE

EN 20250610



MODEL

HED-WF

HED-4G(CN)

HED-4G(EU)

HED-LAN

ELECTRICAL DATA

Power Supply DC 4.5 - 18V

GENERAL DATA

Max. Number of Inverters	1			
Inverter Communication Interface	RS485			
Antenna	Internal Integrated			
Ethernet Interface	/	/	/	LAN (100Mbps)
LED Indicator	1 (for Web Status)			
Serial Communicaiton Rate / bps	9600			
Communicaiton Distance / m	<=100	<=100	/	<=100
Data Intervals	5 Mins (0.5-5Mins can be adjusted)			
Parameters Setting	Bluetooth/Web/APP	Web/APP	Web/APP	Web/APP
Data Access	Web server			

ENVIRONMENTAL DATA

Operating Temperature Range / °C	-20 ~ +60			
Operating Humidity	0 ~ 100%			
Storage Temperature Range / °C	-35 ~ +70			
Degree Of Protection	IP65			

MECHANICAL DATA

Dimensions (W*H*D) / mm	97*46*28			
Weight / g	60			

OTHERS

Flame Retardant Grade	UL94 V-0			
UV Protection Grade	F1			
Installation Method	Plug-in			